

Technical data sheet

novaTAPE 132



Composition: Biaxially oriented transparent Polypropylene film, one side coated with acrylic adhesive. Resistant to aging and UV radiation.

Technical specification:

<i>Carrier:</i>	BOPP – Biaxially oriented transparent Polypropylene film
<i>Width:</i>	48 mm ±2 %
<i>Length:</i>	132 m ±5 %
<i>Colours:</i>	brown, transparent, white
<i>Core diameter:</i>	25,4 mm (1")
<i>Backing thickness:</i>	0,025 mm ±5 %
<i>Adhesive:</i>	Base of acrylic polymers with advanced recipes, thickness 0,017 mm ±10 %
<i>Total thickness:</i>	0,042 mm
<i>Elongation:</i>	140,00% ±20 %
<i>Tensile strength:</i>	140 N/25mm ±10 %
<i>Adhesion at 180°</i>	≥ 3,5 (≥2,0) N/25mm ±10 %
<i>Heat resistance:</i>	0°C up to + 40°C

Usage: Ideal for office use. This product has a wide range of applications. However it is advisable to check the use it is meant for, the surface of application and its cleanliness. Thanks to the advanced adhesive recipes this product is very well resistant to aging and UV radiation. Its features ensure long-term adhesion permanency after a tape is applied.

Normally the tapes are not toxic and not irritating to skin contact.

Attention:

The information and recommendations contained in this document derive from the best of our knowledge, data and conviction at the time of publishing this sheet.

The packaging system 1" core is protected by Intellectual Property Office.